


PURICELL_SHAKING 80

Shaking incubator which provides aeration-agitation environment suitable for cell culture



Precise speed control



Sticky pad tray

STANDARD SPECIFICATION



MODEL	PURICELL_SHAKING 80	
Size	Inner(W x D x H)mm	504 x 521 x 385
	Out(W x D x H)mm	543 x 874 x 546
	Platform(W x D)mm	445 x 445
	Weight(Kg)	100
Controller	Standard : Digital PID controller, Auto-tuning	
Inside Material	Stainless steel plate 304	
Outside Material	Epoxy powder coated steel plate	
Door Material	Polycarbonate	
Lamp	LED lamp	
Temperature	Range	15°C ~ 65°C
	Wait On Timer	59m.59s / 59h.59m / continuous
	Sensor Type	PT 100Q
	Control	Forced convection(Direct heating & cooling)
Compressor	1/6HP, R-134a, Non-CFC	
Shaker	Motion	Clockwise
	Speed Range	20~300 RPM at floor / 20~200 RPM at table
	Wait Off Timer	59m.59s / 59h.59m / continuous
	Throw	20mm
Power	230V±10%, 50Hz, EU Standard Plug	
Power Consumption	Max 2,500W	
Safety	Over heat protector, Thermal rocker-actuated circuit breaker, Heat protective barrier of controller box, Cooling fan for motor	
Cat. No.	CS-PCS-8-R-MB_5Z	
For 230V±10%, 60Hz	CS-PCS-8-R-MB_6Z	

MAIN FEATURE



Transparent plastic door for easy observation

By applying a transparent cover of polycarbonate material, the door can be opened / closed smoothly and it's easy to observe inside.



LEDs that do not affect the temperature inside the chamber

light makes it easier to observe the chamber without affecting the internal chamber temperature with a low heat LED light inside.



Shaking incubator with refrigeration


The built-in refrigeration system is designed for widely supporting from low temperature experiment to high temperature.



A variety of options for shaking platform


Different style of shaking platform is available based on user's requirement.

FEATURE PLUS Optional Tray depending on various shaking platform




Universal tray + Sticky pad

- It has advantage that free space arrangement is possible regardless of flask size.



Spring Rack

- Flask can be fixed by spring wire and various sizes of flask can be fit.



Universal tray + Steel flask holder

The flask can be hold by fitting a flask holder by size.


<Max capacity of flask holder>

Flask Size	2L	1L	500ml	250ml	100ml
Capacity	5EA	7EA	16EA	25EA	45EA

SAFE GUARD

Electrical safety design

- There is no risk of electrical leakage in spite of sample's spillage because of the leakage-proof design of bottom plate
- Because controller and main board are installed in the isolated drawer box, it is electrically safe and easy for maintenance.



ORDER INFORMATION

DIVISION	ITEM	PURICELL SHAKING 80
		Cat. No.
PRODUCT	With 50Hz Condition	CS-PCS-8-R-MB_5Z
	With 60Hz Condition	CS-PCS-8-R-MB_6Z
OPTION	Spring Rack(453x453mm)	CS-PCS-8-R-CO-SR
	Universal Tray(445 x 445mm) Without Sticky Pad	CS-PCS-8-R-CO-TO
	Sticky Pad(4EA/SET)	CS-PCS-8-R-CO-SP
	Flask Holder 100ml(Stainless)	CS-PCS-CO-FH100
	Flask Holder 250ml(Stainless)	CS-PCS-CO-FH250
	Flask Holder 500ml(Stainless)	CS-PCS-CO-FH500
	Flask Holder 1000ml(Stainless)	CS-PCS-CO-FH1000
	Flask Holder 2000ml(Stainless)	CS-PCS-CO-FH2000
	Wooden Packing	CS-CO-50060